



W. MAASS NEDERLAND, ISO 9001 APPROVED BY LLOYD'S SINCE 1988

ALL OUR PRODUCTS ARE MANUFACTURED BY REPUTABLE
MANUFACTURERS, ACCEPTED BY BY ALL MAJOR CHEMICAL, PETRO CHEMICAL
AND OFFSHORE COMPANIES.



W. Maass Nederland BV

P.O. Box 129, Veilingweg 32 2650 AC Berkel en Rodenrijs Holland

Telephone +31-10-511 66 33, Telefax +31-10-511 79 92

E-mail sales@wmaass.nl

www.wmaass.nl



W. Maass Nederland BV

321 / 321 H

**BUTT WELD FITTINGS AND
FORGED FLANGES**

WORLD'S LARGEST AND MOST COMPREHENSIVE STOCKHOLDER OF 321/321 H BUTT WELD FITTINGS AND FORGED FLANGES.

COMPLETE STOCK BUTT WELD FITTINGS



ELBOWS 45, 90, 180 DEGREES LONG AND SHORT RADIUS

CONCENTRIC AND ECCENTRIC REDUCERS

EQUAL AND REDUCING TEES

CAPS

WALL THICKNESS SCHEDULE 10S, 40S, 80S, 120, 160
AND SCHEDULE XXS

SEAMLESS AND WELDED EXECUTION



SEAMLESS EXECUTION

SIZES 1/2" NB. UP TO AND INCLUDING 18" NB.

WELDED EXECUTION

SIZES 10" NB. UP AND INCLUDING 24" NB.

CERTIFICATION:

EN10204/3.1 AND ISO 9001

ADDITIONAL TESTING

PMI, LIQUID DYE PENETRATION, ULTRASONIC, CHARPY IMPACT,
CORROSION AND HARDNESS TESTING CAN BE PERFORMED IN ONE DAY.



COMPLETE STOCK OF FLANGES, FORGED FITTINGS AND O'LETS

**WELDING NECK AND BLIND 150, 300, 600, 900, 1500
and 2500 LBS TO ASME B16.5**

SIZES 1/2"NB. UP TO AND INCLUDING 24" NB.
SCHEDULE 10S, 40S, 80S, 120, 160 AND XXS



WELDING NECK 5000 AND 10000 PSI TO API6A

SIZES 1/2"NB. UP TO AND INCLUDING 24" NB.
SCHEDULE 10S, 40S, 80S, 120, 160 AND XXS



SOCKET WELD 150, 300, 600, 900 AND 1500 LBS

SIZES 1/2" UP TO AND INCLUDING 6"
SCHEDULE 10S, 40S, 80S, 120, 160 AND XXS



LAP JOINT, SLIP ON 150, 300, 600 LBS

SIZES 1/2"NB. UP TO AND INCLUDING 24" NB.



FORGED 3000 AND 6000 LBS FITTINGS

SOCKET WELD AND SCREWED EXECUTION.
SIZES 1/2" UP TO AND INCLUDING 3"

WELDOLETS, SOCKOLETS AND THREADOLETS

SIZES 1/2" UP TO AND INCLUDING 6"

ADDITIONAL TESTING

WE ARE FAMILIAR WITH ADDITIONAL TESTING AND CERTIFICATION IN ACCORDANCE WITH
SPECIFIC CUSTOMERS REQUIREMENTS AS WELL AS NATIONAL AND INTERNATIONAL
STANDARDS.

UPON REQUEST ALL MATERIALS CAN BE SUPPLIED IN STABILIZED HEAT TREATED
CONDITION.

